

Duck Patch

A high performance, professional grade repair product



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

A high performance, professional grade repair product that cures to a long lasting rubber-like film. This product remains flexible through extreme temperature ranges. Its non-sag property and exceptional adhesion makes this an ideal cement for vertical or horizontal construction and repair of all flashings, metal joints, seams, coping, vent pipes, skylights, chimneys, breaks in roofing, bonded roof shingles, foundations, parapet walls, gutters, concrete, & SBS roof systems. This product is ideally suited for sealing cracks, holes, and tears in built-up roofs and modified bitumen single plys.

Note: Do not use on Single Ply Rubber Roofs

Application

All surfaces to be treated must be free from oil, grease and other foreign materials prior to application. The surface must be firm and free from loose material. On composition roofs, open any breaks or blisters to be patched and permit to dry out before applying this product.

Trim Nozzle to desired bead size. Puncture foil at innerbase of nozzle. Using a caulking gun, apply to a minimum wet thickness of 1/4". Allow at least 24 hours to dry (32 °F or higher and less than 50% humidity with no rain) before applying a surface coating. Use above or below grade. Coverage will vary with thickness of application but will approximate 30 lineal feet per cartridge (1/4" thick.) Clean up tools and hands with waterless hand cleaner

Clean Up

Xylene.

Precautions

- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 gm/liter max
- KEEP OUT OF REACH OF CHILDREN
- CAUTION! COMBUSTIBLE
CONTAINS PETROLEUM DISTILLATE. Keep away from heat, spark and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. USE WITH ADEQUATE VENTILATION.

Meets or exceeds SS-C-153 Type I, ASTM D-4586 TYPE I, & ASTM D-3409