

Duck Coat Dry Seal

Rubberized Liquid Coating for Superior Waterproofing



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

An elastomeric polymer modified asphalt emulsion designed for coating concrete foundations. Protects concrete foundations from moisture and water intrusion. Dries black.

Uses

- Primer for Self-Adhered Foundation Membrane
- Seals & Water-Proofs:
 - Concrete
 - Wood
 - Foamboard
 - Exterior Basement Walls
 - Polystyrene/Styrofoam
 - Insulation Board
 - Concrete Walls (Block or Poured)

Surface Preparation

For best results, surface shall be clean, dry and free of any dirt or contaminants.

Application

Stir container thoroughly. Apply using either a brush or airless spray unit (suggested tip size .021 to .025). Apply material at a rate of 150 square feet per 4.75 gallon pail. Allow material to dry and cure for 24 hours prior to application of foam or drainage boards or backfilling.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean tools with water before material dries.

Weather Conditions

Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.

In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop

coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.

Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

Approximately 30 square feet per gallon pail at 60 mils thickness.

Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 0 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Water	7732-18-5
Polymer	N/A
Asphalt	8052-42-4

Duck Coat Dry Seal - Rubberized Liquid Coating for Superior Waterproofing

Revised: 08/20